

ABNOX PNEUMATIC FILLING DEVICE (5:1) FOR 25KG DRUMS CONICAL

Model: 4446510



Description

ABNOX pneumatic filling device (5:1) for 25 kg conical barrels

Container capacity (kg)	25
Container internal dia (mm)	306 – 335
Height of the container (mm)	406
Suction tube dia (mm)	32
Suction tube length (mm)	473
Min. / Max. temperature (°C)	10 / 40
Specification for operating medium	Lubricants up to NLGI 1 / 5,000 m Pa.s
Output pressure (average) at working pressure 6 bar [bar]	27
Output pressure (average) at working pressure 10 bar [bar]	45
Delivery speed pro double stroke (cm3)	20
Supply speed at pump outlet [cm3 / min]	1500
Min. / Max. inlet working pressure [bar]	2 / 10
Inlet operating pressure (compressed air) optimum [bar]	6
Max air consumption [l / min.]	150
Connection (compressed air) internal thread	½ BSP
Connection (average) External wire P	½ BSP

Smeertechniek Rotterdam

Cairostraat 74

3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

