



## ABNOX PNEUMATIC FILLING DEVICE (5:1) FOR 180KG DRUMS

Model: 4447500



### Description

ABNOX pneumatic filling device for 200 kg barrels without protective sleeve.

Capacity container (kg)	180
Container inside dia (mm)	560 - 600
Height of container (mm)	850
Suction tube dia (mm)	32
Length suction tube (mm)	845
Min. / Max. temperature (°C)	10 / 40
Specification for operating medium	Lubricants up to NLGI 1 / 5,000 m Pa.s
Output pressure (average) at working pressure 6 bar [bar]	27
Output pressure (average) at working pressure 10 bar [bar]	45
Delivery speed pro double stroke (cm <sup>3</sup> )	20
Delivery speed pro double stroke (cm <sup>3</sup> )	1500
Min. / Max. inlet working pressure [bar]	2 / 10
Inlet operating pressure (compressed air) optimum [bar]	6
Max air consumption [l / min.]	150
Connection (compressed air) internal thread	½ BSP
Connection (average) External wire P	½ BSP

#### Smeertechniek Rotterdam

Cairostraat 74  
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E [info@smeertechniek.nl](mailto:info@smeertechniek.nl)

W [www.smeertechniek.nl](http://www.smeertechniek.nl)

Scan the QR code to  
order this product

