


STRAIGHT INTERMEDIATE COUPLING Ø4 MM LL

Model: 1010-04LL



Description



DIN 2353	Ø	PN BAR			L1	l1	REF.		
		Fe	Cu/Zn	316Ti			Fe/Zn	Cu/Zn	AISI 316Ti
LL	4	100		100	31	12	1010-04LL		3010-04LL
	6	100		100	32	9	1010-06LL		3010-06LL
	8	100		100	35	12	1010-08LL		3010-08LL
L	6	500	160	315	39	10	1010-06L	2010-06L	3010-06L
	8	500	160	315	40	11	1010-08L	2010-08L	3010-08L
	10	500	160	315	42	13	1010-10L	2010-10L	3010-10L
	12	400	160	315	43	14	1010-12L	2010-12L	3010-12L
	15	400	160	315	46	16	1010-15L	2010-15L	3010-15L
	18	400	160	315	48	16	1010-18L	2010-18L	3010-18L
	22	250	80	160	52	20	1010-22L	2010-22L	3010-22L
	28	250	80	160	54	21	1010-28L	2010-28L	3010-28L
	35	250	80	160	63	20	1010-35L	2010-35L	3010-35L
	42	160	80	160	66	21	1010-42L	2010-42L	3010-42L
S	6	630	250	630	45	16	1010-06S	2010-06S	3010-06S
	8	630	250	630	47	18	1010-08S	2010-08S	3010-08S
	10	630	250	630	49	17	1010-10S	2010-10S	3010-10S
	12	630	250	630	51	19	1010-12S	2010-12S	3010-12S
	14	630	250	630	57	22	1010-14S	2010-14S	3010-14S
	16	420	180	400	57	21	1010-16S	2010-16S	3010-16S
	20	420	180	400	66	23	1010-20S	2010-20S	3010-20S
	25	420	180	400	74	26	1010-25S	2010-25S	3010-25S
	30	420	180	400	80	27	1010-30S	2010-30S	3010-30S
	38	315	120	315	90	29	1010-38S	2010-38S	3010-38S

Smeertechniek Rotterdam

Cairostraat 74

3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

