
ELECTRIC OIL DRIPPER METB-3000.2 PLEXIGLASS 24V DC 14

Model: 0211 11 0240 02 0



Description

Electrically controlled multipledrip feed lubricator for oil and other liquids.
Solenoid valve (»open-closed« function) - distributing battery (1 - 10 drip feed lubricators) - exact drop dosing by metering spindles - large replenishing bowl with screw-type for or filler cap - cylinder glass of PLEXIGLAS or nature glass - easy visual inspection of drop fall.

With the electric multiple UNI drip feed lubricator MET.B up to 10 lubricating points can centrally be supplied through the installed valve battery, whereby the requested oil quantity can be set for each individual lubricating point by means of the installed drip feed lubricators and supplied to them through pipes an hoses.

The »open-closed« function can be controlled directly through the main switch of the machine.

Type	A	B	C	Inhoud (ml)	vulopening	elektr. aansl.
MET.B 140	175	60	60	140	schroefdop	24 V, 50 Hz
MET.B 200	195	80	80	200	schroefdop	24 VDC
MET.B 500	235	100	80	500	tankdop	48 V, 50 Hz
MET.B 1000	275	120	100	1000	tankdop	220 V, 50 Hz
MET.B 2000	320	150	133	2000	tankdop	220 V, 60 Hz
MET.B 3000	350	180	150	3000	tankdop	andere spanningen op aanvraag

Smeertechniek Rotterdam
Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan the QR code to order this product