PRESSOL PLASTIC OILER 300 ML WITH BRASS DOUBLE PUMP

Model: 04 903



Description

Specification

- Angled spout ALU (00 220)
- Double-acting brass pump (DWMP)
- Ball bearing mounted and gravity controlled suction tub, enables containers to be almost completely emptied
- Pump enables drip feed
- All valves are ball valve type
- Pump, with 2 ball valves
- Sealing mechanism, with drip collector pan
- Impact-proof and robust
- Ergonomic design
- High surface quality

Volume of container (ml)	300
Material of container	HDPE (high density polyethylene)
Colour of container	white, transparent
Material of pump	brass + zinc
Volume per stroke pump (ml/stroke)	1
Length of spout (mm)	165
Material of spout	aluminium
Height (mm)	320
Base LxB (mm)	85 x 70
Weight (kg)	0,28

General data

Weight (kg)	0,27

Technical data

Measurements LxWxH (mm)	125 x 60 x 320
Content (ml)	300.000
Color	white, transparant

Smeertechniek Rotterdam
Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan the QR code to order this product

Lenght	165 mm (aluminium)
Material	plastic (high density)
Output (ml)	1

Smeertechniek Rotterdam
Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan the QR code to order this product