



PRESSOL METAL OILER 750 ML WITH FLEX AND RIGID SPOUT

Model: 05 226



Description

Specification

- Angled spout ALU (01 071)
- Angled spout enables lubricating in difficult to access locations
- Superflex spout, transparent (01 130)
- Single-acting brass pump (EWMP)
- Pump enables drip feed
- All valves are ball valve type
- Pump, with 2 ball valves
- High surface quality, lacquered with environment-friendly water based paint

Volume of container (ml)	750
Material of container	steel
Lacquering of container	blue, RAL 5010
Material of pump	brass
Volume per stroke pump (ml/stroke)	1
Length of spout (mm)	135
Material of spout	aluminium
Length superflex spout	210
Material of flex spout	PVC
Height (mm)	200
Base LxB (mm)	150 x 100
Weight (kg)	0,33

General data

Weight (kg) 0,33

Technical data

Measurements LxWxH (mm) 150 x 100 x 200

Content (ml) 750

Color blue, RAL 5010

Length Rigid spout = 135 mm (aluminum) || flexible spout = 210 (PVC)

Scan the QR code to
order this product

Smeertechnik Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechnik.nl

W www.smeertechnik.nl



Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

