



## PRESSOL ONE-HAND GREASE GUN 500CCM, M10X1 WITH ACCESSORIES

Model: 12 254



## **Description**

#### Specifications:

Filling nipple (FN), M 10 x 1 male (12 670)

Grease gun head, zinc die casting Z 410

Dismantleable and movable push rod system

Ergonomic handle

Hydraulic coupler, M 10 x 1 female (12 631)

Spout, straight, M 10 x 1, 150 mm (12 435)

High pressure hose, M 10 x 1 male, 11 x 300 mm, with 4-claws-coupler, M 10 x 1 female (12  $655\,810$ )

#### Special notes:

Operates with greases up to NLGI grade 2 at 20°C

The construction allows a single hand operated lubrication for an easy work in restricted areas

Can be switched with the hand grip from grease delivery with high volume to high pressure Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions

Damaged cartridges can easily be removed

Push rod can be locked in any position - push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)

The ease of dismantling permits simple cleaning

Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns

High-speed ventilation, by half a rotation of the grease gun tube

Designed for use in rough conditions

Similar to DIN 1283

#### General data

Weight (kg)

1.2

Scan the QR code to order this product

**T** 010 - 466 62 55

3047 BC Rotterdam

Cairostraat 74

**F** 010 - 466 66 55

E info@smeertechniek.nl

Smeertechniek Rotterdam

W www.smeertechniek.nl



# **Technical data**

Connection	M10x1
Pressure (bar)	max. 300
Yield (gr)	1,1 per stroke
Refilling options	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Capacity (cm³)	500

### Smeertechniek Rotterdam

Cairostraat 74 3047 BC Rotterdam

**T** 010 - 466 62 55 **F** 010 - 466 66 55

**E** info@smeertechniek.nl

**W** www.smeertechniek.nl

Scan the QR code to order this product

