PRESSOL ONE-HAND GREASE GUN 125CCM, G1/8 WITH ACCESSORIES

Model: 12 276



Description

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Spout, straight, G 1/8 a, 150 mm (12 475)
- Coupler, 4 jaws, G 1/8 (12 731)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Contoured plunger, tight fitting, with bulk grease
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Safe handle on the push rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease
- High-speed ventilation, by half a rotation of the grease gun tube

Technical data	
Grease gun connection, pressure-side	G 1/8
Filling nipple	M 10 x 1
Capacity (cm^3)	125
Refilling options	grease gun filling system or bulk grease
Diameter of grease piston (mm)	8
Grease pump piston actuation	manual, by means of pressure grip
Delivery rate/stroke (cm^3)	0,4
Discharge pressure up to (bar)	550
Burst pressure system (bar)	850
Burst pressure grease gun head (bar)	1200
Operation of push rod	with L-design handle
Cover	loose
Wall thickness of grease gun tube (mm)	1,0
Lacquering	silver
Dimensions LxWxH (mm)	275 x 145 x 55
Weight (kg)	0,53

Smeertechniek Rotterdam
Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan the QR code to order this product