

PRESSOL PNEUMAXX ONE-HAND GREASE GUN M10X1 WITH ACCESSORIES

Model: 12 282



Description

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- High pressure hose, M 10 x 1 male, 11 x 300 mm (12 655)
- Spout, straight, M 10 x 1, 150 mm (12 435)
- 2 precision machined couplers, 4 jaws, M 10 x 1 female (12 643)
- Empty cartridge, 400 g (12 519)

Special notes

- Suitable for all high performance lubricants for industrial use and thickest BIO greases up to NLGI 3, at a grease temperature until -10 °C
- Pneumatic grease supply to the grease gun head by compressed air at 4 bar pressure
- Traditional compression spring mechanism is replaced by a pneumatic system, operating problems will be reduced to a minimum, no grease can get behind the piston seal.
- Due to the safety and pressure relief valves the grease gun can be stored pressure free.
- Precision accuracy of fit of pump piston and cylinder (no false lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Low effort required for lubrication due to optimum lever efficiency

General data

Weight (kg)	1..5
--------------------	------

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

