

PRESSOL STANDARD GREASE GUN, M 10 X 1 + G1/8

Model: 12 638 782



Description

Specification

Filling nipple (FN), M 10 x 1 male (12 670)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Separate filling and ventilation valves on grease gun head
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- The ergonomic handle of the plunger rod assists in overcoming the spring load
- Slip resistant handle on grease gun lever
- Fixed cap, with clamp
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

General data

Weight (kg)	1,34
--------------------	------

Technical data

Measurements LxWxH (mm)	400 x 140 x 75
--------------------------------	----------------

Burst pressure (bar)	850
-----------------------------	-----

Smeertechniek Rotterdam

Cairostraat 74

3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



Pressure (bar)	400
Transport volume/stroke (cm³)	1,2 bij 400 bar tegendruk
Refilling options	400g grease cartridge, DIN 1284, grease filler or bulk grease with use of spatula
Capacity (cm³)	500

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

