



PRESSOL LEVER GREASE GUN 500 CC - G1 / 8 ELITE WITH ACCESSORIES

Model: 12 676 040



Description

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- High pressure hose, G 1/8 male, 11 x 300 mm (12 755)
- Retention adapter, G 1/8 female, M 10 x 1 male (12 016)
- Spout, angled, G 1/8, 150 mm (12 735)
- 2 x Coupler, 4 jaws, G 1/8 (12 743)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Designed for use in rough conditions, wall thickness grease gun tube: 1 mm
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston, cylinder and O-ring with 6 fit (no dummy lubrication)
- No dummy (apparent) lubrication. Sealing system: O-ring and ball valve prevent grease compressed in the grease gun head from feeding back.
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- The ergonomic handle of the plunger rod assists in overcoming the spring load
- Slip resistant handle on grease gun lever
- Enables even under extreme backpressure, a variable lubrication pressure with steady effort applied
- Allows lubrication in difficult to reach locations because the smallest lever operation results in grease being pumped reliably to the lubrication point.
- Damaged cartridges can easily be removed
- Push rod can be locked in any position - push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)
- High-speed ventilation, by half a rotation of the grease gun tube

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Technical data

Scan the QR code to
order this product



Grease gun connection, pressure-side through a steel adaptor	M 10 x 1, G 1/8
Filling nipple	M 10 x 1
Capacity (cm ³)	500
Refilling options	400 g grease cartridge, DIN 1284, grease filling system or loose grease using a spatula
Diameter of grease piston (mm)	9
Grease pump piston actuation	manually lever operated
Delivery rate/stroke (cm ³)	proportional to the manual lever operating distance, max. 1,6
Discharge pressure up to (bar)	600
Burst pressure system (bar)	850
Burst pressure grease gun head (bar)	1200
Operation of push rod	with T-grip
Cover	loose
Wall thickness of grease gun tube (mm)	1
Surface treatment	all steel components are galvanized
Weight (kg)	1,54

Technical data

Connection	M 10 x 1, G 1/8" through metal adaptor
Burst pressure (bar)	850
Pressure (bar)	600
Transport volume/stroke (cm³)	proportioneel t.o.v. de handhefboomafstand, max. 1,6
Refilling options	400g grease cartridges, DIN 1284, grease filler or bulk grease with use of a spatula
Capacity (cm³)	500

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

