

PRESSOL STANDARD GREASE GUN, HHFP, G1/8, WITH ZBH, CBOX

Model: 12 733 804



Description

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- High pressure hose, G 1/8 male, 8 x 300 mm (12 756)
- Coupler, 4 jaws, G 1/8 (12 731)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

General data

Weight (kg) 1.28

Technical data

Connection G1/8"

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



Burst pressure (bar)	850
Pressure (bar)	400
Transport volume/stroke (cm³)	1.2
Refilling options	400g grease cartridge, DIN 1284, or bulk grease
Capacity (cm³)	500

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

