



PRESSOL CARTER SYRINGE 1000 ML. TYPE ELITE

Model: 12 932



Description

Specifications:

- Oils up to SAE 90, screen cleaners, cooling agents, petroleum, brake fluid, water up to 80° C, fuel oil, diesel
- Suction tube (12 944)
- Transparent flexible hose (12 954)
- Double plunger (12 955)

Special notes:

- Oils up to SAE 90, screen cleaners, cooling agents, petroleum, brake fluid, water up to 80° C, fuel oil, diesel
- Even after 30.000 filling and discharging processes 100% suction power.
- The double plunger provides a safe suction of the liquid.
- Ergonomic T-grip
- Strong curls provide a safe operation.
- All liquid operated parts are high quality nickel plated.

Materials of parts in contact with liquid:

End cap	zinc nickel plated
Casing	nickel plated steel
Piston	LDPE (polyethylene of low density)
Support plate	PAGF 30 (PP glass-fibre reinforced)
Suction pipe	aluminium, anodised
Flexible hose	PVC

Technical data

Suction volume (%)	100
--------------------	-----

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



Tube thickness (mm)	1
Stroke length	450 mm
Capacity (cm³)	1000

Specificaties

Shank diameter	13 mm outer
Hose	ø13mm/ 470 mm

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

