

PRESSOL CARTER SYRINGE 750 ML. ALUMINIUM

Model: 12 963



Description

Specifications:

- Ergonomic T-grip
- Suction hose (12 996)

Special notes:

For mineral, synthetic and biological oils, commercially available fuels such as gasoline, diesel and ethanol, heating oil, kerosene, antifreeze (window and motor), glycerin, urea up to 10 %, water and seawater.

The plunger ensures reliable suction of the liquid.

All materials that come into contact with the media are of high quality.

Materialen van delen die in aanraking komen met media:

Head and cover	PAGF 30 (PP glass-fibre reinforced)
Tube	aluminium
Piston	FKM (Viton®)
Piston rod	stainless steel
Valves / connection	aluminium
Suction hose	PVC

General data

Weight (kg) 0,61

Technical data

Suction volume (%) 100

Measurements LxWxH (mm) 95 x 65 x 435

Tube thickness (mm) 1,5

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



Outer diameter (mm)	Tube = 60
Stroke length	400 mm
Capacity (cm³)	750

Specificaties

Hose	ø18 / 600 mm
-------------	--------------

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

