



PRESSOL CARTER SYRINGE 500 ML. ALUMINUM, DOUBLE ACTING

Model: 12 980



Description

Specifications:

- Ergonomic T-grip
- Suction hose (12 997)
- Discharge hose (12 998)

Special notes :

For mineral, synthetic and biological oils, commercially available fuels such as gasoline, diesel and ethanol, heating oil, kerosene, antifreeze (window and motor), glycerin, urea up to 10 %, water and seawater.

The plunger ensures reliable suction of the liquid.

All materials that come into contact with the media are of high quality.

Materials of parts in contact with liquid:

Head and cover	PAGF 30 (PP glass-fibre reinforced)
Tube	aluminium
Piston	FKM (Viton®)
Piston rod	stainless steel
Valves / connection	aluminium
Valve ball	PTFE
Suction hose	PVC
Discharge hose	PVC

General data

Weight (kg) 0,55

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



Technical data

Suction volume (%)	100
Measurements LxWxH (mm)	95 x 65 x 350
Tube thickness (mm)	1,5
Stroke length	300 mm
Capacity (cm ³)	500

Specificaties

Shank diameter	18 mm
Shank length	600 mm
Hose	ø20/600 mm

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

