



# PRESSOL CARTER SYRINGE 750 ML. PVC, DOUBLE ACTING

Model: 12 986



## Description

### Specification:

- Ergonomic T-grip
- Suction hose (12 997)
- Discharge hose (12 998)

### Special notes :

For mineral, synthetic and biological oils, diesel, heating oil, antifreeze (window and motor), glycerin, urea up to 10%, water and seawater.

The plunger ensures reliable suction of the liquid.

All materials that come into contact with the media are of high quality.

### Materials of parts in contact with liquid:

Head and cover	PAGF 30 (PP glass-fibre reinforced)
Tube	PVC
Piston	FKM (Viton®)
Piston rod	stainless steel
Valves / connection	aluminium
Valve ball	PTFE
Suction hose	PVC
Discharge hose	PVC

## Technical data

<b>Suction volume (%)</b>	100
<b>Tube thickness (mm)</b>	3
<b>Outer diameter (mm)</b>	Tube = 60

### Smeertechniek Rotterdam

Cairostraat 74  
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E [info@smeertechniek.nl](mailto:info@smeertechniek.nl)

W [www.smeertechniek.nl](http://www.smeertechniek.nl)

Scan the QR code to  
order this product



<b>Content (ml)</b>	750
---------------------	-----

<b>Stroke length</b>	400 mm
----------------------	--------

## Specificaties

<b>Shank diameter</b>	18 mm
-----------------------	-------

<b>Shank length</b>	600 mm
---------------------	--------

<b>Hose</b>	Afgifte= $\varnothing$ 20 / 600mm
-------------	-----------------------------------

### **Smeertechniek Rotterdam**

Cairostraat 74

3047 BC Rotterdam

**T** 010 - 466 62 55

**F** 010 - 466 66 55

**E** [info@smeertechniek.nl](mailto:info@smeertechniek.nl)

**W** [www.smeertechniek.nl](http://www.smeertechniek.nl)

Scan the QR code to  
order this product

