



PRESSOL ONE-HAND GREASE GUN FN-BLACK - M10 X 1.0

Model: 14 400 211



Description

Specifications:

Filling nipple (FN), M 10 x 1 male (12 670)

Galvanized parts: grip, lever, pulling strap, safety catch, cap, push rod

Grease gun head, zinc die casting Z 410

Dismantleable and movable push rod system

T-grip, optimized grip and pressure optimized

Ergonomic handle, non-slip, excellent power transfer and handling

Grease gun also available in the colors silver, red, blue, green and yellow

Special notes:

The construction allows a single hand operated lubrication for an easy work in restricted areas

Can be switched with the hand grip from grease delivery with high volume to high pressure Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions

Damaged cartridges can easily be removed

Push rod can be locked in any position - push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)

The ease of dismantling permits simple cleaning

Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns

High-speed ventilation, by half a rotation of the grease gun tube

Designed for use in rough conditions

Similar to DIN 1283

Technical data

Connection M10x1

Smeertechniek Rotterdam

Cairostraat 74 3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to order this product



Pressure (bar)	max. 300
Transport volume/stroke (cm³)	1,1
Refilling options	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Capacity (cm³)	500

Smeertechniek Rotterdam

Cairostraat 74 3047 BC Rotterdam

T 010 - 466 62 55 **F** 010 - 466 66 55

E info@smeertechniek.nl **W** www.smeertechniek.nl

Scan the QR code to order this product

