



PRESSOL MOUTHPIECE ASSORTMENT BOX G1/8

Model: 17 023 125



Description

- 1 MULTIBOxx 050
- 1 button head coupler for flat grease nipples, 22 mm / 0,86, DIN 3404, M22, G 1/8 female (12 063 125)
- 3 button head couplers, for button head grease nipple, slide-on type, 16 mm / 0,62, DIN 3404, M1 + T1, G 1/8 female (12 061 125)
- 3 button head couplers for button head nipples 16 mm / 0,62 DIN 3404, M1 + T1, G 1/8 female (12 062 125)
- 3 button head couplers, for button head grease nipple, 10 mm / 0,39, DIN 3404, M4, G 1/8 female (12 060 125)
- 5 hydraulic couplers, 4 jaws, G 1/8 female (12 731)
- 5 precision machined couplers, 4 jaws, G 1/8 female (12 743)
- 5 hollow/universal couplers, R 1/8 a, for H- and K-nipples (12 072)
- 5 pointed couplers, R 1/8 female, for funnel type grease nipples (12 073)
- 5 filling nipples, for grease gun head, M 10 x 1 male, Ø = 9 mm (12 670)
- 3 angles 90°, G 1/8 female, G 1/8 male (12 035 805)
- 5 universal couplers, for push type guns, M 10 x 1 female (12 071)
- 5 reducing sockets, G 1/8 female, M 10 x 1 male (12 016)
- 5 reducing sockets, R 1/8 male, M 10 x 1 female (12 086)
- 5 spouts, straight, G 1/8 male, 150 mm (12 475)
- 5 spouts, angled, G 1/8 male, 150 mm (12 735)
- 1 wall-mounting bracket, for grease guns (12 699)
- 1 push type gun, 80 ml, steel, set, to suit H, K and D-nipples (12 362)
- 5 seals, for grease gun head, Ø1 = 60,2 mm, Ø2 = 48 mm, S = 2 mm (00 442)
- 5 high pressure hoses, G 1/8 male, 11 x 230 mm (12 751)
- 5 quick release adapters, M 10 x 1 female (12 006)
- 5 sleeves, G 1/8 female, G 1/8 female (18 017)
- 3 swivel joints, 1 x 360°, G 1/8 a, G 1/8 female (18 080)

Smeertechnik Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechnik.nl

W www.smeertechnik.nl

Scan the QR code to
order this product



Technical data

Thread size

G1/8"

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

