

PRESSOL PNEUMATIC GREASE GUN 500 CC WITH EXTENSION PIPE AND H-HEAD

Model: 18 071



Description

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Angled spout, M 10 x 1, 150 mm (12 635)
- Coupler, 4 jaws, M 10 x 1 (12 631)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Plunger with exactly fitting when using bulk grease or cartridge
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the push rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- High-speed ventilation, by half a rotation of the grease gun tube

Grease gun connection, pressure-side	M 10 x 1
Filling nipple	M 10 x 1
Capacity (cm³)	500
Refilling options	400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Pressure ratio	50:1
Grease supply into the grease gun head	spring operated
Diameter of grease piston (mm)	6
Grease pump piston actuation	single-stroke grease supply
Delivery rate/stroke (cm³)	0,8
Recommended air pressure (bar)	6
Min. air pressure (bar)	2
Max. air pressure (bar)	8
Compressed air connection	hose nozzle, 6 mm, for hose, DN 6 (20 132)
Pump pressure at 8 bar air pressure (bar)	400
Burst pressure system (bar)	850
Burst pressure grease gun head (bar)	1200
Operation of push rod	with L-design handle
Cover	loose
Wall thickness of grease gun tube (mm)	1,0
Lacquering	silver
Weight (kg)	1,84

Smeertechniek Rotterdam

Cairostraat 74

3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product



General data

Weight (kg)	2.0
-------------	-----

Technical data

Connection	M10x1
------------	-------

Burst pressure (bar)	850
----------------------	-----

Pressure (bar)	400
----------------	-----

Transport volume/stroke (cm ³)	0.8
--	-----

Refilling options	400g grease cartridges, DIN 1284, grease filler or bulk grease
-------------------	--

Capacity (cm ³)	500
-----------------------------	-----

Smeertechniek Rotterdam

Cairostraat 74

3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

