



PRESSOL OPEN HOSE REEL WITH 10 MTR. HD HOSE, CEILING

Model: 29 252



Description

Specification

- Open, for mounting on ceilings
- With hose stop

Special notes

- Pressol hose reels are exceedingly robust and are notable for their compact design
- All metal parts are phosphatized, undercoated and painted
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum
- The hose can be engaged by rotating 1/4 turn

Length of discharge hose (m)	10
Connection discharge hose	G 1/4 female/male
Length of connecting hose (m)	1
Connection to connecting hose	G 1/4 female/female
Inner diameter of hose (DN)	6
Operating pressure max. (bar)	400

Arm	window grey, satin, RAL 7040
Supporting plate	window grey, satin, RAL 7040
Encasing	blue, Pantone 294 C
Angled mounting bracket	blue, Pantone 294 C
Dimensions LxWxH (mm)	475 x 158 x 520
Weight (kg)	20,4

Smeertechnik Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechnik.nl

W www.smeertechnik.nl

Scan the QR code to
order this product



General data

Usage open, voor plafondmontage, met slangstop

Technical data

Connection 1/4" BSP bi/bui

Lenght 10 meter

Max pressure (bar) 400

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

