



PERMA STAR FILLING 250 CM3 SF01 UNIVERSAL GREASE

Model: 2-104473



Description

PERMA STAR VARIO 2.0

- Battery supply
- Application temperature -10 to +60 °C
- Transparent reservoir
- Choice of 12 delivery periods: 1, 2, 3, ..., 12 months
- Lubrication delivery is individually adjustable with every change of the LC unit
- LED signaling on the motor unit (eg in operation, empty, error message)
- Available 60, 120 and 250 cm³
- Insulation value: IP65

PERMA STAR CONTROL 2.0

With this system, the correct amount of lubricant can be dispensed very precisely per lubrication point.

There are 36 Time functions from 0.6 to 34 cm³ per 100 operating hours and 99 Impulse functions from 0.1 to 9.5 cm³ per Impulse from the PLC.

- Control current: 9-30 volts
- Reservoirs: 60, 120 and 250 cm³
- Operating temperature: -20 to +60 °C
- Pressure build-up: 6 bar
- Insulation value: IP65
- Machine controlled or PLC controlled
- Alarm notification via LED and PLC
- This system is suitable for oils and lubricants up to NLGI 2.

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

