



PRESSOL PNEUMATIC PUMP 5:1, DW, NEF, INSTALLATION SET

Model: 19 335 600



Description

Specification

- installation set
- For 200/220 I container
- Pneumatic oil pump 5:1 (19 335)
- Double-acting pump, provides a continuous flow of media
- Suction tube, G 3/4 male
- Compressed air hose, 2 m, DN 9, with male quick connecting adapter, for Rectus coupling, type 26
- Oil discharge hose, 2 m, G 1/2 male/female, lever ball valve, G 1/2 female
- Air maintenance unit (20 218 950)
- With all adapters required for assembly
- Designed for use in conjunction with pipe lines. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar).
- Can be easily combined with several hose reels
- Suction tube length: 860 mm
- Compressed air connection: Plug nipple for coupling Rectus, type 26, NW 7.2 mm
- Pressure side connection: G1/2 bu
- Container connection: G2 male, barrel screw connection
- Weight: 8.88 kg

Smeertechniek Rotterdam

Cairostraat 74 3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to order this product

