PRESSOL FOOT OPERATED GREASE PUMP MOBILE, 15 KG

Model: 17 793



Description

Specification

- High pressure grease hose, 11 x 1500 mm
- Spout, angled, M 10 x 1, 150 mm
- Coupler, 4 jaws, M 10 x 1 (12 631)
- Manual shut-off valve
- 2 fixed wheels and robust adjustable foot
- Lacquering, oil-resistant
- Robust moving handle
- Pump, grease follow-up piston, with spring

Capacity of container (kg)	15
Container diameter	220
Container height	380
Pumping media	lubricating greases, up to NLGI 2
Delivery rate/stroke (cm³)	8 with NLGI 1
Discharge pressure up to (bar)	150
Discharge	utilizing a foot pump
Filling	manual, utilizing a removable filling cap
Discharge hose	high pressure hose, 11 x 1500 mm
Material pump body	aluminium
Material pump head	steel
Lacquering of container	window grey, satin, RAL 7040
Weight (kg)	10
Capacity of container (kg)	15
Container diameter	220
Container height	380
Pumping media	lubricating greases, up to NLGI 2
Delivery rate/stroke (cm³)	8 with NLGI 1
Discharge pressure up to (bar)	150

Smeertechniek Rotterdam
Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan the QR code to order this product