

PRESSOL PUMP FOR PLASTIC JERRYCANS 20LITER

Model: 17 019 950



Description

Specification

- Discharge hose, 1500 mm, NBR, with textile insert (17 003)
- Barrel screw coupling, for plastic container, height adjustable (19 519)
- Steel discharge spout, with lever ball valve (13 096)
- For oils, up to SAE 140, self-lubricating, non-aggressive media

Delivery rate (l/stroke)	0,05
Delivery rate at 60 strokes/min (l/min)	3
Barrel screw coupling, female thread	M 62,5 x 4 female
Pumping media	oils, up to SAE 140
Usage	rectangular 20 l original containers or right angled plastic barrels with external thread (M 62,2 x 4 mm)
Application	for direct filling of gearboxes and difficult to access locations
Discharge	through discharge hose and steel discharge spout with lever ball valve
Length of suction tube (mm)	500
Surface treatment	all steel components are galvanized
Materials of parts in contact with liquid	
Pump head	impact-resistant zinc die casting
Pump body	steel
Seals	NBR
Weight (kg)	2,12

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechniek.nl

W www.smeertechniek.nl

Scan the QR code to
order this product

