



MEER INFORMATIE OVER KABELSMERING

Model: Corelube Kabelsmering



2100-BOS-T1 SYSTEM
Cable Size Range: 0.125" (3.2mm) to 1.88" (47.6mm)



ADVANTAGES

- Easy to use.
- Lubricates wire ropes at speeds of 800 Feet/Minute (244 meters/minute).
- One branch line fits a range of rope sizes. Eliminates the need for a rubber seal for every size of wire rope.
- Wire rope assemblies can be run through the unit.
- Wire ropes can run through the unit at any angle.
- The same pump fits all sizes of containers.

The new CORELUBE 2100-BOS System is designed to apply STRAN-CORE Lubricant.

- STRAN-CORE is an advanced Concrete Adhesive with Extreme Traction and Anti-Slip Properties.
- Grease-like protection in a low viscosity form.
- Clings to surface and penetrates lower levels for maximum protection, traction and grip.
- Long-lasting performance - excellent results on all steel surfaces.
- Non-toxic. Non-flammable and safe.
- Extends lifespan of both Wheel Production and Steel Rope. Add to a 10% - 40% savings.
- STRAN-CORE Lubricant is sold globally from the world's largest Lubricant Manufacturer about 85000 tons.



Omschrijving

Ook voor uw kabelsmering kunt u bij ons terecht. Kabelsmering op maat draagt bij aan de levensduur van uw kabels. Wij hebben onder andere het Corelube systeem 2100-BOS-T1 System en 3100-BOS-R1 System ins ons leveringsprogramma met bijbehorende kabelreinigers zoals de helix groove cleaners.

Mocht u meer informatie willen ontvangen? Een offerte?
Of graag iemand laten meedenken over de beste oplossing?

Neem dan gerust contact met ons op via info@smeertechnik.nl.

3100-BOS HOUSING



Smeertechnik Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55

F 010 - 466 66 55

E info@smeertechnik.nl

W www.smeertechnik.nl

Scan de QR code om
dit product te bestellen



3100-800 SYSTEM
Cable Size Range: 4.0" (10mm) to 3.0" (77mm)

The 3100-800-81 System is designed to apply thick oil, joint grease & soft greases that are self-purging.



ADVANTAGES

- Easy to use.
- Lubricates wire ropes at speeds of 500 Ft./Min.
- One brush does the job of rope sizes. Eliminates the need for a laborer used for every size of wire rope.
- Wire rope deterioration can be less through the unit.
- Wire ropes can run through the unit at any angle.
- The same pump fits all sizes of containers from a drum to a pail.



Accommodates Wire Rope Sizes From: 7/32" (5.5mm) to 2 9/16" (65 mm)

The CORELUBE A-1600-LB3 ADVANTAGE

- The CORELUBE A-1600 System is a high pressure wire rope grease injection unit for NLGI #00, #1, #2 greases.
- The Beads and Backings wrap into the bearing without touch.
- Solid machined housing with dual O-ring seals.
- Removes old lubricant, dirt and grime.
- High Pressure 50:1 Pump.
- High Output Volume Pump 4.38" 150.5mm Air Motor.

SYSTEM INCLUDING:

- (1) A-1600 Applicator Housing
- (1) 50:1 High Output Pump In-line 10-20 Kg Containers
- (1) Drum Cover to fit 10-20 Kg Containers
- (1) Hollow Plug PTC 10-20 Kg Containers
- (1) Seal (dry Seal)
- (1) Breaker / Backing Guide (any size)
- (1) Beads
- (2) Tie Down Restraint Straps
- (1) High Pressure O-Ring Material (O-Ring) with Fittings
- (1) Air Regulator/Filter with Gauge & Valve
- (1) High Pressure Discharge Valve



Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan de QR code om dit product te bestellen



A1500 L700 Groove System

See our A-1500 Seal Size List for complete list of sizes.

Our Groove Cleaners fit all types and sizes of wire-rope from 19 - 7 Outer Strands.

On-Line Volume Calculators

See our Stroke Counter 500000 for more information. Cables Available

CoreLabe Equipment's Helix Groove Cleaners are designed to remove contaminants from the valleys between the strands of wire rope. The cleaner works by rotating with the helical lay of the wire rope.

(HGC) Helix Groove Cleaners

The Helix Groove Cleaners are designed to work with CoreLabe's applicator rollers or thrust block as shown at right.

HELIX GROOVE CLEANER TYPES AVAILABLE:

- Diameter Ranges: 13.0 mm – 127.0 mm
- Number of Outer Strands: 3 – 18
- Left & Right Lay
- Round Stranded Wire Ropes
- Triangular/Strapped Stranded Wire Ropes

See our HGC Order Form & HGC Installation Instructions for more information.

See our Thrust Block options. See our Thrust Block brochure for more information.

SMEERTECHNIEK ROTTERDAM

CoreLabe Equipment's Helix Groove Cleaners are designed to remove contaminants from the valleys between the strands of wire rope. The cleaner works by rotating with the helical lay of the wire rope.

Thrust Block

(HGC) Helix Groove Cleaners

Thrust Block Assembly

HELIX GROOVE CLEANER TYPES AVAILABLE:

- Diameter Ranges: 13.0 mm – 127.0 mm
- Number of Outer Strands: 3 – 18
- Left & Right Lay
- Round Stranded Wire Ropes
- Triangular/Strapped Stranded Wire Ropes

See our HGC Order Form & HGC Installation Instructions for more information.

The purpose of the Thrust Block is to give our groove cleaners a flat abrasive surface to clean against. Guide rollers are ordered in the same size as the wire rope diameter. These are not used to anchor the block with straps or ropes, just contact.

All CoreLabe's lubrication systems come standard with a guide bearing and do not require the thrust block. The thrust block is an option if you want to use a Corbrite lubrication system or changing the rope lay capability from the rope manufacturer.

SMEERTECHNIEK ROTTERDAM

Smeertechniek Rotterdam

Cairostraat 74
3047 BC Rotterdam

T 010 - 466 62 55
F 010 - 466 66 55
E info@smeertechniek.nl
W www.smeertechniek.nl

Scan de QR code om dit product te bestellen

